- 1. A method of displaying alert information in a network, comprising:
- 2 storing performance information for network objects at predetermined time
- 3 intervals; and
- displaying a summary view including a plurality of cells corresponding to
- 5 respective periods of time, the cells including an alert status indication for the network
- 6 objects.

- 8 2. The method according to claim 1, further including displaying a first region
- 9 corresponding to a first network object type, wherein the plurality of cells includes a first
- series of cells providing alert information for one or more objects of the first object type.

11

- 12 3. The method according to claim 2, further including displaying a second region
- corresponding to a second network object type, wherein the plurality of cells includes a
- second series of cells providing alert information for one or more objects of the second
- 15 object type.

16

- 17 4. The method according to claim 3, further including displaying alert information
- for all first object type devices in the first region and for selected ones of the first object
- 19 type devices.

20

- 21 5. The method according to claim 4, wherein the selected ones of the first object type
- correspond to a user-created group of objects.

23

- 24 6. The method according to claim 1, further including displaying a first time/date
- box and a second time/date box, and displaying alert information for a time period
- 26 corresponding to the first time/date box.

- 7. The method according to claim 6, further including displaying alert information
- 2 for a time period corresponding to the second time/date box for comparison to the alert
- 3 information for the first time/date.
- 4 8. The method according to claim 7, further including receiving a date selection for
- 5 the second date.

- 7 9. The method according to claim 1, further including receiving a user selection of
- 8 the predetermined interval for performance data collection.

9

- 10 10. The method according to claim 1, further including receiving a user selection of
- 11 the cell time period.

12

- 13 11. The method according to claim 1, wherein the alert information includes at least a
- 14 no alert status and alert status.

15

- 16 12. The method according to claim 1, wherein the alert information includes at least a
- no alert status, a medium alert status and a critical alert status.

18

- 19 13. The method according to claim 1, further including displaying a topographical
- 20 map including a plurality of regions for displaying respective network object types
- associated with one or more alerts, the map corresponding to a particular cell in the
- 22 summary view.

23

- 24 14. The method according to claim 13, wherein the particular cell is selected by a
- 25 user.

26

- 27 15. The method according to claim 13, further including displaying a graph of
- 28 performance data for one or more of the network objects.

- 1 16. The method according to claim 15, further including displaying a threshold associated with the performance data for the one or more network objects.
- 4 17. The method according to claim 15, further including displaying statistical band
- 5 information for the performance data.
- The method according to claim 1, further including determining at least one root potential root cause of one or more alerts.

8919. An article, comprising:

18

22

- a storage medium having stored thereon instructions that when executed by a machine result in the following:
- storing performance information for network objects at predetermined time intervals;
- determining at least one potential root cause of one or more alerts in the network; and
- displaying a summary view including a plurality of cells corresponding to periods of time, the cells including an alert status indication for the network objects.
- 19 20. The article according to claim 19, further including displaying a first region 20 corresponding to a first network object type, wherein the plurality of cells includes a first 21 series of cells providing alert information for one or more objects of the first object type.
- 21. The article according to claim 20, further including displaying a second region 24 corresponding to a second network object type, wherein the plurality of cells includes a 25 second series of cells providing alert information for one or more objects of the second 26 object type.
- 28 22. The article according to claim 20, further including displaying alert information 29 for all first object type devices in the first region and for selected ones of the first object 30 type devices.

- 23. 1 The article according to claim 19, further including displaying a first date box and 2 a second date box, and displaying alert information for the first date. 3 24. The article according to claim 23, further including displaying alert information 4 5 for the second date for comparison to the alert information for the first date. 6 25. The article according to claim 19, further including receiving a user selection of 7 the cell time period. 8 9 26. The article according to claim 19, wherein the alert information includes at least a 10 no alert status and alert status. 11 12 27. The article according to claim 19, further including displaying a topographical 13 map including a plurality of regions for displaying respective network object types 14 15 associated with one or more alerts, the map corresponding to a particular cell in the summary view. 16 17 28. 18 The article according to claim 27, further including displaying a graph of performance data for one or more of the network objects. 19 20 29. 21 The article according to claim 28, further including displaying statistical band information for the performance data. 22 23 30. :24 The article according to claim 28, further including displaying performance data for a metric selected by a user. 25
- 27 31. A computer system, comprising:
- a processor;

a display coupled to the processor; and

1 a memory coupled to the processor; wherein the memory includes stored 2 instructions that when executed result in the following: storing performance information for network objects at predetermined time 3 intervals; 4 5 determining at least one potential root cause of one or more alerts in the network; and 6 displaying a summary view including a plurality of cells corresponding to periods 7 of time, the cells including an alert status indication for the network objects. 8 9 32. 10 The system according to claim 31, further including displaying a first region 11 corresponding to a first network object type, wherein the plurality of cells includes a first 12 series of cells providing alert information for one or more objects of the first object type. 13 33. The system according to claim 32, further including displaying a second region 14 corresponding to a second network object type, wherein the plurality of cells includes a 15 second series of cells providing alert information for one or more objects of the second 16 object type. 17 18 34. The system according to claim 33, further including displaying alert information 19 20 for all first object type devices in the first region and for selected ones of the first object 21 type devices. 22 35. 23 The system according to claim 31, further including displaying a first date box and 24 a second date box, and displaying alert information for the first date. 25 36. 26 The system according to claim 35, further including displaying alert information 27 for the second date for comparison to the alert information for the first date. 28

The system according to claim 31, further including receiving a user selection of

37.

the cell time period.

29

- 1 38. The system according to claim 31, wherein the alert information includes at least a
- 2 no alert status and alert status.

- 4 39. The system according to claim 31, further including displaying a topographical
- 5 map including a plurality of regions for displaying respective network object types
- 6 associated with one or more alerts, the map corresponding to a particular cell in the
- 7 summary view.

8

- 9 40. The system according to claim 39, further including displaying a graph of
- 10 performance data for one or more of the network objects.

11

- 12 41. The system according to claim 40, further including displaying statistical band
- information for the performance data.

- 15 42. The system according to claim 40, further including displaying performance data
- 16 for a metric selected by a user.